



MORE THAN 500 DESIGN FILMS

SPECIFICATIONS:

Calendered Vinyl Film with Polymeric
Adhesive Coating
Thickness: 200 to 350 micron

Width: 1220 mm
Tear resistance :
Length: 5.1 kgf/cm - Length: 6.9 kgf/cm
Extension: Up to 220%
Excellent resistance to abrasion, acid
(Ethanol, salt), stains, dirt, mold... except Xylene

Dilation after 48 hours at 65 °C
Width: 0.9% - Length: 0.6%
Resistant to traction
Width: 262 kg/cm Length : 230 kg/cm

ADHESIVE:

Acrylic and activated, moisture insensitive.
This film is applied on clean, smooth, rigid and
non-porous surfaces (glass, metal, plastics,
painted wood...)

ADHESIVE FORCE:

20 min after installation: 1.04 kg/cm
24 hours after installation: 1.43 kg/cm
3 days after installation: 1.51 kg/cm
7 days after installation: 1.65 kg/cm

ADHESIVE STRENGTH HIGH TEMPERATURE 70 C°:

During one day: 1.37 kg/cm
During 7 Days: 1.03 kg/cm

IDEAL INSTALLATION TEMPERATURE:

20 °C to 25 °C (min. 12 °C and max 35 °C)
Dry application using a suitable scraper.
The removal of the film is possible using a heat gun.

Available languages FR - DE - ES - IT - PL - RU - TR - PT ↓

FURTHER INFORMATION : WWW.COVERSTYL.COM



FUTURA →

DESIGN FILMS

+ 45 DESIGNS

DISCOVER ALL FILMS :
WWW.SOLARSCREEN.EU

+ 20 COLOURS



COLOUR FILMS

← BLUE 40C

Prodotto Distribuito

FI ORE

VISUAL COMUNICATION MATERIALS

www.fioretorino.com



U19

Authorized Installer

COVER STYL'

Smart Interior Design

FI ORE Srl

